

Power: 5kW

Energy Stored: 20kWh

redT 5-20 Technical Data

Product Image



Dimensions

Container	6'6" Hi-Cube Container
L x W x H	2000 x 2438 x 2896 mm
Front Door Clearance	2000mm
Weight (Dry)	2000kg
Weight (Filled)	3400kg


Certifications

Safety & EMC Standard	EN50178, EN62109-1, EN61000-6-2, EN61000-6-4
Country of Manufacture	UK
QMS	ISO 9001
Environmental	ISO 14001
Workmanship	IPC Class 3
Warranty	Available with remote monitoring subscription


System Performance

Rated Power	5kW
Nominal Voltage	48V
Rated Current (Output)	125 Amps
Energy Capacity	20kWh
DC/DC Efficiency	70-75%
Standby Self-Consumption	<50W
Usable Depth of Discharge	100%
System Life	>25 Years
Operating Temperature Range †	-20°C - 35°C*
* (Unpowered)	
** (With Climate Control)	-25 °C - +55°C**
† Average temp. over 24h	

Example SLD



Charge/Discharge Characteristics



FOR ADDITIONAL INFORMATION AND GUIDANCE, CONTACT OUR TECHNICAL SALES TEAM

T +44 (0)207 061 6233 E enquiries@redTenergy.com W redTenergy.com

*Specifications subject to change without notice